


Kalstein A different accompaniment, at your service

LABORATORY LINESph Meters





All rights reserved ® KALSTEIN France S. A. S., 2 Rue Jean Lantier • 75001 Paris • +33 1 78 95 87 89 / +33 6 80 76 07 10 • https://kalstein.eu KALSTEIN FRANCE, S. A. S





OUR SERVICES

Benefits and Support

In Kalstein France, we take care of the full satisfaction of our customers, that is why we provide value-added services of the highest level based on our experience.



Online Inductions and Trainings

In any part of the world, receive your induction or training from our specialized team of engineers



Quick Response

Our work team is always available to response all your consults or questions, in order to support you in any situation.





#Letsgivemore 💗

Thanks to your purchase, a donation is made to a non-profit foundation that fights against cancer and helps vulnerable communities.



Technical Support

Enjoy of personalized advice for the correct preventive and corrective maintenance of your equipment, thanks to Kalstein's manuals and articles, special catalogues and video tutorials.





Delivery Logistics

We take care of all the necessary logistics for the dispatch of your goods, whether is by sea, land or.air.



Kalstein Worldwide

With more than 25 years growing with our customers, Kalstein's multiformat and modern content, is now present in more than 10 countries and increasing.







Portable Sodium Ion Meter

Model YR01817-8











Professional portable sodium ion meter, suitable for outdoor applications, accuracy: 0.5% F.S.

Features:

- ✓ Professional portable sodium ion meter is equipped with a backlit LCD display.
- ✓ 2 to 5 points calibration from low to high concentrations.
- ✓ Selectable 8 concentration calibration points, including the 0.001 to 10000.
- ✓ Selectable concentration units ppm, mg/L and mol/L.
- ✓ Automatic temperature compensation ensures accurate readings over the entire range.
- ✓ Direct ion concentration readout simplifies the measurement
- ✓ Auto-Read function senses and locks the measurement
- ✓ Calibration due alarm prompts user to calibrate the meter
- ✓ Auto-Power Off effectively conserves battery life.
- ✓ Setup menu allows setting the number of calibration points, stability criteria, temperature

- unit, date and time, etc.
- Reset function automatically resumes all settings back to the factory defaults.
- ✓ Expanded memory stores or recalls up to 500 data sets.
- ✓ USB communication interface for data transfer or connecting a power adapter to meter.

Accessories

- ✓ ISE-Na sodium electrode
- ✓ TP-10K temperature probe
- ✓ Automatic electrode diagnosis shows the calibration points and ✓ Sodium standard solutions 100, 1000 ppm
 - ✓ Ionic strength adjuster
 - Carrying case

Optional Accessories:

- ✓ ISE-Na Sodium Electrode Range: 0.002 to 69000 ppm
- ✓ TP-10K Temperature Probe: For temperature compensation and measurement
- ✓ Ion Standard Solutions: For ion concentration calibration
- ✓ Ionic Strength Adjusters: For adjusting the pH and background ionic strength
- ✓ USB Cable: For transferring data or connecting power adapter
- ✓ 5V DC Power Adapter: For connecting external power source

KALSTEIN FRANCE, S. A. S



#Letsgivemore



Thanks to your purchase, a donation is made to a non-profit foundation that fights against cancer and helps vulnerable communities.



All rights reserved ® KALSTEIN France S. A. S. 2 Rue Jean Lantier • 75001 Paris • +33 1 78 95 87 89 / +33 6 80 76 07 10 • https://kalstein.eu







Portable Sodium Ion Meter

Model YR01817-8





Model	YR01817-8
Ion Concentration	
Range Resolution Accuracy Calibration Points Calibration Solutions Measurement Units	0.002 to 69000 ppm 0.001, 0.01, 0.1, 1, automatic ±0.5% F.S. 2 to 5 points 0.001 / 0.01 / 0.1 / 1 / 10 / 100 / 1000 / 10000 ppm, mg/L, mol/L, mmol/L
mV	
Range Resolution Accuracy	-1999.9 to 1999.9 mV 0.1 mV ±0.2 mV
Temperature	
Range Resolution Accuracy Offset Calibration Calibration Range	0 to 105°C / 32 to 221°F 0.1°C/°F ±0.5°C / ±0.9°F 1 point Reading ±10°C/°F
Other Specifications	
Temperature Compensation Hold Function Stability Criteria Calibration Due Alarm	0 to 100°C / 32 to 212°F, manual or automatic Manual / Auto-read measurement endpoint Low / High 1 to 31 days or off
Auto-Power Off Memory Output Connector	10 / 20 / 30 minutes after last key pressed Stores up to 500 data sets USB communication interface
Display Power Supply Battery Life	BNC, 3.5 mm jack socket Custom LCD (80 × 60 mm) 3 × 1.5V AA batteries or 5V DC power adapter Approximately 150 hours without backlight
Environmental Conditions Dimensions	0 to 50°C / 32 to 122°F, relative humidity < 80% 170 × 85 × 30 mm 300 g
Weight	300 y



#Letsgivemore 💗

Thanks to your purchase, a donation is made to a non-profit foundation that fights against cancer and helps vulnerable communities.



All rights reserved ® KALSTEIN France S. A. S., 2 Rue Jean Lantier • 75001 Paris • +33 1 78 95 87 89 / +33 6 80 76 07 10 • https://kalstein.eu

KALSTEIN FRANCE, S. A. S







#LETSGIVEMORE >

WITH THE ADCQUISITION OF A KALSTEIN EQUIPMENT

YOU MAKE A CONTRIBUTION TO:





https://onetreeplanted.org



Solidarité et coopération biomédicale

https://www.humatem.org/



https://www.maniapurefoundation.org/



ANY DOUBT? Contact us!

Articles Kalstein

(Social Networks and Official Websites)







Article of the week: How does the climate affect your microscope?

Read more on Kalstein's social medias or official websites





Article of the week: What is the importance of the laboratory refrigerator?

Read more on Kalstein's social medias or official websites https://kalstein.eu/articles



PARIS - FRANCE HEADQUARTER

2 Rue Jean Lantier 75001 Paris - France

Tlf: +33 (0) 01 78 95 87 89 **Cel:** +33 (0) 6 80 76 07 10 sales@kalstein.eu

https://kalstein.eu/ https://www.kalstein.fr/



(Youtube Channel and Official Websites)



Kalstein France - Jacinto Convit Foundation / Allianc...

23 views • 3 years ago



Kalstein's Microscopes

445 views • 1 week ago

