

LABORATORY LINES pH METERS





All rights reserved ® KALSTEIN France S. A. S., Optimum Business Center 450 Rue Baden Powell, • 34000 Montpellier, France. TIF: +33 467158849 / +33 660760710/ +33 663810023 https://kalstein.eu KALSTEIN FRANCE, S. A. S





our services Benefits and Support

In Kalstein France, we take care of the full satisfaction of our customers, that is why we provide value-added services of the highest level based on our experience.



Online Inductions and Trainings In any part of the world, receive your induction or training from our

specialized team of engineers



Quick Response Our work team is always available to response all your consults or questions, in order to support you in any situation.



#Letsgivemore Thanks to your purchase, a donation is made to a non-profit foundation that fights against cancer and helps vulnerable communities.



Technical Support

Enjoy of personalized advice for the correct preventive and corrective maintenance of your equipment, thanks to Kalstein's manuals and articles, special catalogues and video tutorials.



Delivery Logistics We take care of all the necessary logistics for the dispatch of your goods,

whether is by sea, land or.air.



Kalstein Worldwide

With more than 25 years growing with our customers, Kalstein's multiformat and modern content, is now present in more than 10 countries and increasing.









KALSTEIN® Benchtop Multiparameter

Model Series YR01836



YR01836 Benchtop pH/Conductivity Meter

High-accuracy multiparameter water quality meter contains 12 options, the meter is suitable for measuring the pH, mV, conductivity and total dissolved solids.

рΗ

- Multiparameter water quality meter is equipped with a 6.5 inches backlit LCD display
- \checkmark 1 to 5 points calibration with automatic recognition for USA, NIST and DIN buffers \checkmark
- ✓ Automatic electrode diagnosis shows the pH slope and offset ORP

1 point offset calibration allows adjusting the displayed value to a known standard Relative and absolute millivolt modes ensure the reliable ORP measurements Ion Concentration

- ✓ 2 to 5 points calibration, including the 8 concentration points can be selected
- ✓ Direct ion concentration readout simplifies the measurement process
- ✓ Automatic electrode diagnosis shows the calibration points and slopes
- ✓ Selectable concentration units (ppm, mg/L, mol/L, mmol/L) and ionic valency

Conductivity/TDS/Salinity/Resistivity

- ✓ 1 to 5 points calibration with automatic recognition for conductivity standards
- Selectable cell constant, reference temperature, TDS factor, linear and pure water
- ✓ compensations, seawater and practical salinity measurement modes
- ✓ Automatic electrode diagnosis shows the calibration points and factors

Dissolved Oxygen

- ✓ 1 or 2 points calibration using the air-saturated water or zero oxygen solution
- ✓ Salinity and barometric pressure compensations eliminate the measurement error

General Features

- Automatic temperature compensation ensures accurate readings over the entire range
- ✓ Auto-Read function senses and locks the measurement endpoint
- ✓ Calibration due alarm prompts user to calibrate the meter regularly
- \checkmark Setup menu allows setting the number of calibration points, resolution, stability

criteria,

- ✓ temperature unit, date and time, etc.
- ✓ Reset function automatically resumes all settings back to the factory defaults
- \checkmark Expanded memory stores or recalls up to 500 data sets
- USB communication interface for data transfer and timed interval readings

YR01835: pH/conductivity/dissolved oxygen electrodes, temperature probe, pH buffer sachets, conductivity standard solutions, DO electrolyte solution, membrane cap, electrode holder, USB cable and power adapter

YR01836/YR01836-1: pH/conductivity electrodes, temperature probe, pH buffer sachets, conductivity standard solutions, electrode holder, USB cable and power adapter

YR01837-1: pH /dissolved oxygen electrodes, temperature probe, pH buffer sachets, DO electrolyte solution, membrane cap, electrode holder, USB cable and power adapter

YR01837: Conductivity /dissolved oxygen electrodes, temperature probe, conductivity standard solutions, DO electrolyte solution, membrane cap, electrode holder, USB cable and power adapter

- ✓ YR01835: pH, mV, relative mV, ion concentration, conductivity, TDS, salinity, resistivity, DO, temperature
- ✓ YR01836: pH, mV, conductivity, TDS, temperature
- YR01836-2: pH, mV, relative mV, conductivity, TDS, salinity, resistivity, temperature
- ✓ YR01837-2: pH, mV, relative mV, DO, temperature
- ✓ YR01837: Conductivity, TDS, salinity, resistivity, DO, temperature



#Letsgivemore 🔍

Thanks to your purchase, a donation is made to a non-profit foundation that fights against cancer and helps vulnerable communities.

All rights reserved (8) KALS TEIN France S. A. S., Optimum Business Center 450 Rue Baden Powell, • 34000 Montpellier, France. Tit: +33 467158849 / +33 660760710/ +33 663810023 https://aistein.eu KALSTEIN FRANCE, S.A. S



www.kalstein.eu

KALSTEIN® Benchtop Multiparameter

Model Series YR01836

| ÷ | Model | | YR01835 | YR01836 | YR01836-1 | YR01837-2 | YR01837 |
|----------------|--------------------------------|---|---------|---------|-----------|-----------|---------|
| | Range | -2.000–20.000pH | • | • | • | • | _ |
| Æ | Resolution | 0.001, 0.01, 0.1pH, selectable | • | • | • | • | _ |
| | Accuracy | ±0.002pH | • | • | • | • | _ |
| | Calibration Points | 1 to 5 points | • | • | • | • | _ |
| | pH Buffer Options | USA, NIST, DIN, 2 custom buffers | • | • | • | • | _ |
| ORP | Range | ±1999.9mV | • | • | • | • | _ |
| | Resolution | 0.1, 1mV, selectable | • | • | • | • | _ |
| | Accuracy | ±0.2mV | • | • | • | • | _ |
| | Calibration Points | 1 point | • | _ | • | • | _ |
| | Range | 0.001~19999 (deponding on the range of ISE) | • | _ | _ | _ | _ |
| | Resolution | 0.001, 0.01, 0.1, 1 | • | _ | _ | _ | _ |
| s | Accuracy | ±0.5% F.S. (monovalent), ±1% F.S. (divalent) | • | _ | _ | _ | _ |
| | Measurement Units | ppm, mg/L, mol/L, mmol/L | • | _ | _ | _ | _ |
| | Calibration Points | 2 to 5 points (0.001, 0.01, 0.1, 1, 10, 100, 1000, 10000) | • | _ | _ | _ | _ |
| 2 | Range | 0.01~20.00, 200.0, 2000µS/cm, 20.00, 200.0mS/cm | • | • | • | | • |
| | Resolution | 0.001, 0.01, 0.1, 1 | • | • | • | | • |
| | Accuracy | ±0.5% F.S. | • | • | • | _ | |
| Conductivity | Calibration Points | 1 to 5 points | • | • | • | _ | • |
| | Calibration Solutions | 10µS/cm, 84µS/cm, 1413µS/cm, 12.88mS/cm, 111.8mS/cm | • | • | • | _ | |
| | Temperature Coefficient | Linear (0.0~10.0%/°C), pure water | • | • | • | _ | |
| | | 20/25°C | • | | • | _ | |
| | Reference Temperature | | • | • | • | _ | • |
| | Cell Constant | K=0.1, 1, 10 or custom | | | | _ | |
| | Range | 0-10.00, 100.0, 1000ppm, 10.00, 200.0ppt | • | • | • | _ | • |
| 1DS | Resolution | 0.01, 0.1, 1 | • | • | • | _ | • |
| | Accuracy | ±1% F.S. | • | • | • | _ | • |
| | TDS Factor | 0.1~1.0 (default 0.5) | • | • | • | _ | • |
| <i>≧</i> | Range | 0.00-42.00psu, 0.00-80.00ppt | • | _ | • | _ | • |
| Salir | Resolution | 0.01 | • | _ | • | — | • |
| | Accuracy | ±1% F.S. | • | _ | • | _ | • |
| DO Resistivity | Range | 0.00-20.00ΜΩ | • | — | • | _ | • |
| | Resolution | 0.01, 0.1 | • | _ | • | _ | • |
| | Accuracy | ±1% F.S. | • | — | • | — | • |
| | Range | 0.00-20.00mg/L, 0.0-200.0% saturation | • | _ | _ | • | • |
| | Resolution | 0.01mg/L, 0.1% | • | — | — | • | • |
| | Accuracy | ±0.2mg/L, ±2.0% | • | _ | _ | • | • |
| | Calibration Points | 1 or 2 points | • | — | — | • | • |
| | Barometric Pressure Correction | 60.0-112.5kPa/450-850mmHg, manual | • | _ | — | • | • |
| | Salinity Correction | 0.0-50.0g/L, manual | • | — | — | • | • |
| 3 | Temperature Compensation | 0–100°C/32–212°F, manual or automatic | • | • | • | • | • |
| al Sp | Memory | 500 data sets, USB communication interface | • | • | • | • | • |
| ener | Power Requirements | DC5V power adapter | • | • | • | • | • |
| | Dimensions and Weight | 210 (L)×188 (W)×60 (H) mm, 1.5kg | • | • | • | • | • |



#Letsgivemore 💚

Thanks to your purchase, a donation is made to a non-profit foundation that fights against cancer and helps vulnerable communities.



All rights reserved (8) KALSTEIN France S. A. S., Optimum Business Center 450 Rue Baden Powell, • 34000 Montpellier, France. Tit: +33 467158849 / +33 680760710/ +33 663810023 https://aidelin.eu KALSTEIN FRANCE, S.A. S



www.kalstein.eu





#LETSGIVEMORE

WITH THE ADCQUISITION OF A KALSTEIN EQUIPMENT YOU MAKE A CONTRIBUTION TO:





https://onetreeplanted.org





ANY DOUBT?

Contact us!

Articles Kalstein (Social Networks and Official Websites)





MONTPELLIER - FRANCE **H E A D Q U A R T E R** Optimum Business Center, 450 Rue Baden Powell, 34000 Montpellier - France.

Fax: +33 (0) 4 67 15 88 49 **Tlf:** +33 (0) 6 80 76 07 10 sales@kalstein.eu

https://kalstein.eu/ https://www.kalstein.fr/

Official Websites for Latin America.



Kalstein Training Videos (Youtube Channel and Official Websites)



Kalstein France - Jacinto Convit Foundation / Allianc...

23 views • 3 years ago



Kalstein's Microscopes 445 views • 1 week ago