

LABORATORY LINES pH METERS









our services Benefits and Support

In Kalstein France, we take care of the full satisfaction of our customers, that is why we provide value-added services of the highest level based on our experience.



Online Inductions and Trainings In any part of the world, receive your

induction or training from our specialized team of engineers



Quick Response Our work team is always available to response all your consults or questions, in order to support you in

any situation.



#Letsgivemore V

Thanks to your purchase, a donation is made to a non-profit foundation that fights against cancer and helps vulnerable communities.



Technical Support

Enjoy of personalized advice for the correct preventive and corrective maintenance of your equipment, thanks to Kalstein's manuals and articles, special catalogues and video tutorials.



Delivery Logistics

We take care of all the necessary logistics for the dispatch of your goods, whether is by sea, land or.air.



Kalstein Worldwide

With more than 25 years growing with our customers, Kalstein's multiformat and modern content, is now present in more than 10 countries and increasing.









Portable Cyanide Ion Meter Model YR01817-4





CE





Portable Ion Meter

Professional portable cyanide ion meter, suitable for outdoor applications, accuracy: 1% F.S.

Features:

- ✓ Professional portable cyanide ion meter is equipped with a backlit LCD display.
- \checkmark 2 to 5 points calibration from low to high concentrations.
- ✓ Selectable 8 concentration calibration points, including the 0.001 Accessories to 10000.
- ✓ Selectable concentration units ppm, mg/L and mol/L.
- ✓ Automatic electrode diagnosis shows the calibration points and slopes.
- ✓ Automatic temperature compensation ensures accurate readings over the entire range.
- ✓ Direct ion concentration readout simplifies the measurement process.
- ✓ Auto-Read function senses and locks the measurement endpoint. ✓
- ✓ Calibration due alarm prompts user to calibrate the meter regularly.
- ✓ Auto-Power Off effectively conserves battery life.

Thanks to your purchase, a donation is made

to a non-profit foundation that fights against

cancer and helps vulnerable communities.

#Letsgivemore

- ✓ Setup menu allows setting the number of calibration points, stability criteria, temperature unit, date and time, etc.
- ✓ Reset function automatically resumes all settings back to the factory defaults.
- ✓ Expanded memory stores or recalls up to 500 data sets.
- ✓ USB communication interface for data transfer or connecting a power adapter to meter.

- ✓ ISE-CN cyanide electrode
- ✓ TP-10K temperature probe
- ✓ Carrying case

Optional Accessories:

- ✓ ISE-CN Cyanide Electrode
- ✓ TP-10K Temperature Probe and measurement
- Range: 0.03 to 260 ppm For temperature compensation
- Ionic Strength Adjusters For adjusting the pH and background ionic strength
- ✓ USB Cable For transferring data or connecting power adapter
- ✓ 5V DC Power Adapter For connecting external power source



All rights reserved ® KALSTEIN France S. A. S. 2 Rue Jean Lantier • 75001 Paris • +33 1 78 95 87 89 / +33 6 80 76 07 10 • https://kalstein.eu KALSTEIN FRANCE, S. A. S



www.kalstein.eu



All rights reserved © KALSTEIN France S. A. S.,

I

-			
	Model		YR01817
Æ	Range	-2.000~20.000pH	_
	Resolution	0.001, 0.01, 0.1pH, selectable	—
	Accuracy	±0.002pH	_
	Calibration Points	1 to 5 points	—
	pH Buffer Options	USA, NIST, DIN, 2 custom buffers	—
<u>5</u>	Range	0.001~19999 (deponding on the range of ISE)	•
	Resolution	0.001, 0.01, 0.1, 1	•
	Accuracy	±0.5% F.S. (monovalent), ±1% F.S. (divalent)	•
	Measurement Units	ppm, mg/L, mol/L, mmol/L	•
	Calibration Points	2 to 5 points	•
	Calibration Solutions	0.001, 0.01, 0.1, 1, 10, 100, 1000, 10000	•
ORP	mV Range	±1999.9mV	•
	Relative mV Range	±1999.9mV	_
	Resolution	0.1, 1mV, selectable	•
	Accuracy	±0.2mV	•
	Calibration Points	1 point	_
Temperature	Range	0~105°C/32~221°F	•
	Resolution	0.1°C/0.1°F	•
	Accuracy	±0.5°C/±0.9°F	•
	Offset Calibration	1 point, reading ±10°C	•
Other Specifications	Temperature Compensation	0~100°C, manual or automatic	•
	Stability Criteria	Low or high	•
	Calibration Due Alarm	1 to 31 days or off	•
	Slope/Offset Display	Yes	•
	Hold Function	Manual or auto-endpoint	•
	Auto-Off	10, 20 or 30 minutes after last key pressed	•
	Memory	500 data sets	•
	Communication Interface	USB	•
	Connector	BNC, 3.5 mm jack socket	•
	Display	Custom LCD (80×60mm)	•
	Power Requirements	3×1.5V AA batteries or DC5V power adapter	•
	Battery Life	Approximately 150 hours (Turn off the backlight)	•
	Dimensions	170 (L)×85 (W)×30 (H) mm	•
	Weight	300g	•
_			



#Letsgivemore Thanks to your purchase, a donation is made to a non-profit foundation that fights against cancer and helps vulnerable communities.



All rights reserved ® KALSTEIN France S. A. S., 2 Rue Jean Lantier • 75001 Paris • +33 1 78 95 87 89 / +33 6 80 76 07 10 • https://kalstein.eu KALSTEIN FRANCE, S. A. S



www.kalstein.eu





#LETSGIVEMORE

WITH THE **ADCQUISITION OF A KALSTEIN EQUIPMENT**

YOU MAKE A CONTRIBUTION TO:





https://onetreeplanted.org

Humatem Solidarité et coopération biomédicale https://www.humatem.org/



https://www.maniapurefoundation.org/



ANY DOUBT? Contact us!



(Social Networks and Official Websites)





PARIS - FRANCE **H E A D Q U A R T E R** 2 Rue Jean Lantier 75001 Paris - France

Tlf: +33 (0) 01 78 95 87 89 **Cel**: +33 (0) 6 80 76 07 10 sales@kalstein.eu


https://kalstein.eu/ https://www.kalstein.fr/

Kalstein Training Videos (Youtube Channel and Official Websites)



Kalstein France - Jacinto Convit Foundation / Allianc...

23 views • 3 years ago



Kalstein's Microscopes 445 views • 1 week ago

