

LABORATORY SECTOR

SPECTROPHOTOMETER







All rights reserved ® KALSTEIN France S. A. S., 2 Rue Jean Lantier • 75001 Paris • +33 1 78 95 87 89 / +33 6 80 76 07 10 • https://kalstein.eu KALSTEIN FRANCE, S.A.S





OUR SERVICES Benefits and Support

In Kalstein France, we take care of the full satisfaction of our customers, that is why we provide value-added services of the highest level based on our experience.



Online Inductions and Trainings In any part of the world, receive your

induction or training from our specialized team of engineers



Quick Response Our work team is always available to response all your consults or questions, in order to support you in any situation.





#Letsgivemore 💙

Thanks to your purchase, a donation will be made to a non-profit foundation that fights against breast cancer and helps most vulnerable communities.



Technical Support

Enjoy of personalized advice for the correct preventive and corrective maintenance of your equipment, thanks to Kalstein's manuals and articles, special catalogues and video tutorials.



Delivery Logistics


We take care of all the necessary logistics for the dispatch of your goods, whether is by sea, land or.air.



Kalstein Worldwide

With more than 25 years growing with our customers, Kalstein's multiformat and modern content, is now present in more than 10 countries and increasing.









#Letsgivemore 💚


Thanks to your purchase, a donation will be made to a non-profit foundation that fights against breast cancer and helps most vulnerable communities.



All rights reserved ® KALSTEIN France S. A. S., 2 Rue Jean Lantier • 75001 Paris • +33 1 78 95 87 89 / +33 6 80 76 07 10 • https://kalstein.eu KALSTEIN FRANCE, S. A. S



www.kalstein.eu



Product Description:

YR05484 is a 45/0 optical portable desktop spectrophotometer, with 256 pixels dual array CMOS image sensor, imported white board, and gives consideration to the speed of measurement and the convenience of operation. YR05484 is a 45/0 optical portable desktop spectrophotometer, with 256 pixels dual array CMOS image sensor, imported white board, and gives consideration to the speed of measurement and the convenience of operation. It features with repeatability ΔE^* ab easily control within 0.02, and inner instrument errors ΔE^* ab control within 0.15. This accuracy measurement makes it good to use in the lab color accurate analysis and transfer. The YR05484 portable desktop spectrophotometer is also good to measure the brightness factor and color coordinates of traffic signs, markings and reflective films. Including GB 2893 and GB/T 18833 standard colors, it can customize the rectangular tolerance of polygons manually.

Application of YR05484 Portable Desktop Spectrophotometer:

YR05484 portable desktop spectrophotometer color measurement instrument is equipped with a single customized 18/8/4mm measurement diameter, used for accurate color measurement and quality control in plastic electronics, paint and ink, textile and garment printing and dyeing, printing, ceramics and other industries; It can be also used for fluorescence sample measurement. In addition, YR05484 portable desktop spectrophotometer is suitable for measuring the brightness factor and chromaticity coordinate of traffic road signs, marking lines and reflective film. It contains GB 2893 and GB/T 18833 standard colors and it can customize the rectangular tolerance of polygons manually.



Technical Adventages:

- ✓ Adopt combination full spectrum LED light source and UV light source Full band balanced LED light source ensures sufficient spectral distribution in visible light range, avoids the spectral loss of white LED in specific band, ensures the accuracy of instrument measurement speed and measurement results, and professional UV light source ensures more reliable UV testing.
- A variety of color space, a variety of observation light sources YR05484 portable desktop spectrophotometer color measurement instrument provides CIE LAB,XYZ,Yxy,LCh,CIE LUV,s-RGB,βxy, Mussel(C/2) color space, and D65,A,C,D50,F2(CWF),F7(DLF),F10(TPL5),F11(TL84),F12(TL83/U30) light sources, which can meet the special measurement requirements under different measurement conditions.
- Calibration Certificate Each YR05484 spectrophotometer has been verified and tested. After leaving the factory, each instrument is verified according to the measurement standards of authoritative verification departments, and the measurement data are traceable to the National Metro technical Institute to ensure the authority of the instrument test data.
- ✓ Industrial-grade HD touch screen, easy to use user interface Using 7-inch industrial grade HD touch screen, smooth operation, the user interface is easy to use and it makes the operation to become comfortable and convenient.
- ✓ Color management software SQCX quality management software with YR05484 spectrophotometer is suitable for quality monitoring and color data management in various industries. Data the user's color management, compare color differences, generate test reports, provide multiple color space measurement data, and customize the customer's color management.
- ✓ Optional Accessory Micro printer, foot switch, rotating bracket can be freely selected according to the needs.



#Letsgivemore * Thanks to your purchase, a donation

Thanks to your purchase, a donation will be made to a non-profit foundation that fights against breast cancer and helps most vulnerable communities.



All rights reserved ® KALSTEIN France S. A. S. 2 Rue Jean Lantier • 75001 Paris • +33 1 78 95 87 89 /+33 6 80 76 07 10 • https://kalstein.eu KALSTEIN FRANCE, S. A. S



www.kalstein.eu

Technical Description:

Model	
Model	YR05484
Optical Geometry	45/0(45 ring-shaped illumination, 0 degree viewing angle)
	Comply to CIE No.15, GB/T 3978,GB 2893,GB/T 18833,IS07724-1,ASTM E1164,DIN5033 Teil7
Characteristic	Enhanced version spectrophotometer, Customized single aperture Φ 18/8/4 mm diameter aperture, used in laboratory accurate analysis and transmission;
	Used for accurate color measurement and quality control in plastic electronics, paint and ink, textile and garment printing and dyeing, printing, ceramics and other industries; It can be used for fluorescence sample measurement.
	It is used to measure the brightness factor and color coordinates of traffic signs, markings and reflective films. It contains GB 2893 and GB/T 18833 standard colors. It can customize the rectangular tolerance of polygons manually.
Integrating Sphere Size	Φ40mm
Light Source	Combined full spectrum LED light source, UV light source
Spectrophotometric Mode	Flat Grating
Sensors	Silicon photodiode array (double row 40 groups)
Wavelength Range	400~700nm
Wavelength Interval	10nm
Semiband Width	10nm
Measured Reflectance Range	0~200%
Measuring Aperture	Customized single aperture,LAV:Ф18mm/Ф20mm;MAV:Ф8mm/Ф10mm;SAV:Ф4mm/Ф5mm
Specular Component	45/0
Color Space	CIE LAB,XYZ,Yxy,LCh,CIE LUV,s-RGB,HunterLab,βxy,DIN Lab99 Munsell(C/2)
Color Difference Formula	$\Delta E^*ab, \Delta E^*uv, \Delta E^*94, \Delta E^*cmc(2:1), \Delta E^*cmc(1:1), \Delta E^*00, DIN\Delta E99, \Delta E(Hunter)$
	WI(ASTM E313,CIE/ISO,AATCC,Hunter),
	YI(ASTM D1925,ASTM 313),
Other Colorimetric Index	YI(ASTM D1925,ASTM 313), Metamerism Index MI,
Other Colorimetric Index	



#Letsgivemore Thanks to your purchase, a donation will be made to a non-profit foundation that fights against breast cancer and helps most vulnerable communities.



All rights reserved ® KALSTEIN France S. A. S., 2 Rue Jean Lantier • 75001 Paris • +33 1 78 95 87 89 / +33 6 80 76 07 10 • https://kalstein.eu KALSTEIN FRANCE, S. A. S



www.kalstein.eu

All rights reserved © KALSTEIN France S. A. S.,

Observer Angle	2°/10°
Illuminant	D65,A,C,D50,D55,D75,F1,F2(CWF),F3,F4,F5,F6,F7(DLF),F8,F9,F10(TPL5) F11(TL84),F12(TL83/U30)
Displayed Data	Spectrogram/Values, Samples Chromaticity Values, Color Difference Values/Graph, PASS/FAIL Result, Color Simulation, Color Offset
Measuring Time	About 1.8s
Repeatability	Chromaticity value: MAV/SCI, within ΔE^*ab 0.02 (When a white calibration plate is measured 30 times at 5 second intervals after white calibration)
Inter-instrument Error	MAV/SCI, Within ΔE*ab 0.15
	(Average for 12 BCRA Series II color tiles)
Measurement Mode	Single Measurement, Average Measurement(2-99times)
Locating Method	
Dimension Weight	L*W*H=370X240X260mm About 7.8kg
Battery	AC 24V, 3A Power adapter power supply
Illuminant Life Span	5 years, more than 3 million times measurements
Display	7-inch TFT color LCD, Capacitive Touch Screen
Data Port	USB, Bluetooth ®5.0, trigger switch interface
Data Storage	Standard 1000 Pcs, Sample 30000 Pcs
Language	Simplified Chinese, English, Traditional Chinese
Operating Environment	0~40°C, 0~85%RH (no condensing), Altitude < 2000m
Storage Environment	-20~50°C, 0~85%RH (no condensing)
Standard Accessory	Power Adapter, USB Cable, User Guide, PC Software(Download from office website), White and Black Calibration Cavity, Protective Cover, Aperture (Optional Aperture)
Optional Accessory	Micro Printer, Foot Switch, Rotating Bracket
Notes	Technical parameters are only for reference, subject to the actual sale of the product



#Letsgivemore Thanks to your purchase, a donation will be made to a non-profit foundation that fights against breast cancer and helps most vulnerable communities.



All rights reserved ® KALSTEIN France S. A. S., 2 Rue Jean Lantier • 75001 Paris • +33 1 78 95 87 89 / +33 6 80 76 07 10 • https://kalstein.eu KALSTEIN FRANCE, S. A. S







#LETSGIVEMORE

WITH THE ADCQUISITION OF A KALSTEIN EQUIPMENT

YOU MAKE A CONTRIBUTION TO:





https://onetreeplanted.org





ANY DOUBT? Contact us!



Articles Kalstein (Social Networks and Official Websites)





PARIS - FRANCE **H E A D Q U A R T E R** 2 Rue Jean Lantier 75001 Paris - France

Tlf: +33 (0) 01 78 95 87 89 **Cel:** +33 (0) 6 80 76 07 10 sales@kalstein.eu


https://kalstein.eu/ https://www.kalstein.fr/

Kalstein Training Videos (Youtube Channel and Official Websites)



Kalstein France - Jacinto Convit Foundation / Allianc...

23 views • 3 years ago



Kalstein's Microscopes 445 views • 1 week ago

